CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:
Original corner established by : John B. David, Deputy Surveyor
under Contract No. 131 dated June 8, 1869.

Surveyor General Record States: Set stone 16x8x6 for corner to Townships 12 South Ranges 33 & 34 East in mound of stone.

T12S	
R33E	R34E
S36	S31
S1	S6
T13S	
1996	
OPLS2734	

Description of corner evidence found:
Found a stone 15"x9"x4" lying in a mound of stone, dimly marked with 5 grooves and 4 grooves.

REGISTERED
PROFESSIONAL
LAND SURVEYOR
OREGON
SEPTEMBER 19, 1985
JACK L. WATSON
2734
RENEWAL DATE: 6/30/98

Description of monument and accessories set at corner location:
I accept the marked corner stone. At the corner position I set a 2 1/2" x 30" aluminum pipe with attached 2 1/2" aluminum cap, set 10 inches in the ground, surrounded by a mound of stone. I placed the original corner stone in the mound of stone north and alongside the aluminum pipe. The cap is stamped as shown in the diagram.

From which I set new reference points:
A 5/8"x15" iron pin driven to refusal, bears N45°E, 25.00 feet, with attached red plastic cap marked CORNERSTONE SURVEYING, INC.
A 5/8"x15" iron pin driven to refusal, bears S23°E, 42.75 feet, with attached red plastic cap marked CORNERSTONE SURVEYING, INC.
A 5/8"x15" iron pin driven to refusal, bears S45°W, 18.68 feet, with attached red plastic cap marked CORNERSTONE SURVEYING, INC.
A 5/8"x15" iron pin driven to refusal, bears N45°W, 24.48 feet, with attached red plastic cap marked CORNERSTONE SURVEYING, INC.

I used a steel tape and magnetic compass, with 20° E. declination, to tie references.

Witnesses: Corey Watson Date: Sept. 2, 1996

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 1st day of Oct, 1996.
Robert D Baggett by .....
(COUNTY OFFICIAL) (DEPUTY)