


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established by Mark A. Fullerton under General Land Office Contract No. 395 dated May 25, 1881.



J-1

Surveyor General's records state:

North on range line west boundary of sec. 18
80.00 Set basalt stone 22X16X10 for cor. to
sec's 7, 18, 12 & 13 from which
a pine 18 in. dia. brs. N18°W 33 lks.
" " 36 " " " N50°E 27 "
" " 10 " " " S47°E 113 "
"Juniper 12" " " S60°W 112 "

Description of corner evidence found:

Found the original bearing trees: a 42" dbh Ponderosa pine with open face scribing visible but not legible bears North 33° East, 18.0 ft.; a 21" dbh Ponderosa pine with open face visible scribing T14R26S18BT bears South 52° East, 75.7 ft.; a 27" dbh Juniper with open face visible scribing T14R26S13BT bears South 31 1/2° West, 73.7 ft.; a 23" dbh Ponderosa pine with open face visible scribing T14R25S12BT bears North 55° West, 21.9 ft.. Juniper should have been scribed 25 not 26 as found. Corner monument was not found and corner area has been disturbed by tractor logging.


Description of monument and accessories | established to perpetuate the original location of this corner:

At mean location of intersection of record distances from the original bearing trees, set 30 inch long 2 inch I.D. aluminum pipe 10 inches in ground to bedrock with 3 1/4 inch aluminum cap marked as shown:

From which the original bearing trees:

a 42" dbh Ponderosa pine bears North 33° East, 18.0 ft. with open face visible scribing but not legible;
a 21" dbh Ponderosa pine bears South 52° East, 75.7 ft. with open face visible scribing T14R26S13BT;
a 27" dbh Juniper bears South 31 1/2° West, 73.7 ft. with open face visible scribing T14R26S13BT;
a 23" dbh Ponderosa pine bears North 55° West, 21.9 ft. with open face visible scribing T14R25S12BT.

Raised a mound of stones 3 1/2 foot base to top of cap.
Set steel post with sign 54-4 6 feet north of and facing cap.
Painted 6 inch red band and nailed signs 54-3 and 54-4 on all bearing trees.



Magnetic
Declination

22° EAST

I hereby certify the above corner monument was re-established as herein described on AUGUST 10, 1982.

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 23 day of Sept, 1982
Robert H. Blaylock by _____
(COUNTY OFFICIAL) (DEPUTY)

