


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established by Mark A. Fullerton under General Land Office Contract No. 395 dated May 25, 1881.

Surveyor General's records state:
North on line between sec's 16 & 17
40.00 Set basalt stone 14X10X7 in stone mound
for 1/4 sec. cor.



F.B.5 P.54 & 55
L-9

Description of corner evidence found:

At assumed corner location made a thorough search for evidence of the original corner with no success. Corner falls in open area West of and above Payten pack trail about 13 feet East of North-South wire fence. Entire area covered with stone particularly in immediate corner vicinity and area to West. Found no stone mounds nor marked stones in area. Found no evidence indicating any perpetuation of the corner and finally conclude corner is lost and re-establish by single proportion method.

Description of monument and accessories | established to perpetuate the original location of this corner:

At proportionate position as determined by survey swing tie, set 2 1/2 inch O.D. aluminum pipe 30 inches long 10 inches in ground to bedrock with 3 1/4 inch aluminum cap marked as shown:

Marked new bearing trees:


a 9" Juniper bears North 66°00' East, 32.9 ft.,
scribed-1/4S16BT;
a 19" Juniper bears South 12°00' West, 62.0 ft.,
scribed-1/4S17BT.

Raised stone mound 4 foot diameter to cap. Painted red band and faces red and nailed signs 54-3 and 54-4 to bearing trees.

Set steel post 5 feet South with sign 54-4 facing corner.
Nailed brass washer stamped-AS&E LS1026-to face of new bearing trees.

I hereby certify the above corner monument was re-established as herein described on September 3, 1984.

Witnesses: David B. Armstrong
Lynn Bruno



M.V.18°30'E.

Office of Surveyor County of Greene
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 23 day of Nov, 1984
David B. Armstrong by _____
(COUNTY OFFICIAL) (DEPUTY)

