


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established by Mark A. Fullerton under General Land Office Contract No. 395 dated May 25, 1881.

Surveyor General's records state:

North on line between sec's 21X22
40.00 Set basalt stone 30X17X10 in stone mound for
1/4 sec. cor.



P-13

Description of corner evidence found:

Found basalt stone 29"X14"X10" set 12" in ground (upright and leaning south) in stone mound of 7 other stones. Stone appears to be faintly marked on north face but not legible. Stone mound was about 2 1/2 foot diameter.

Description of monument and accessories established to perpetuate the original location of this corner:

As the evidence in the corner vicinity agrees with the G.L.O. original record, at the location of the found original stone in mound of stones, set 30 inch long 2 inch I.D. aluminum pipe 8 inches in ground to bedrock with 3 1/4 inch aluminum cap marked as shown:

Marked new bearing tree:


an 8" dbh Juniper bears North 69° East, 56.6 ft.
scribed 1/4S22BT;

Marked new bearing object:

top rock of basalt outcropping 10ft.X6ft.X4ft. high
marked "EP" on east face bears North 81° West, 95.0 ft..

Painted red circle around chisel marks.

Nailed brass washer marked "LS 1026" in lower blaze.



Magnetic Declination

20° EAST

Raised a mound of stones 3 foot base to top of cap and buried the original stone EAST of cap.
Set steel post with sign 54-4 5 feet NORTH of and facing cap.
Painted 6 inch red band and faces red and nailed signs 54-3 and 54-4 on all bearing trees.

I hereby certify the above corner monument was re-established as herein described on JULY 30, 1982.

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 3 day of Sept, 1982
Robert H. Dyer by David B. Armstrong
(COUNTY OFFICIAL) (DEPUTY)

