


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established by Mark A. Fullerton under General Land Office Contract No. 395 dated May 25, 1881.

Surveyor General's records state:

North on line betw. sec's 22X23
40.00 Set basalt stone 14X12X10 in stone mound for
1/4 sec. cor.



Description of corner evidence found:

Found a basalt stone 14"X12"X9" in stone mound 2 1/2 ft.
diameter marked " $\frac{1}{4}$ S" on west face.


Description of monument and accessories | established to perpetuate the
original location of this corner:

As the evidence in the corner vicinity agrees with the G.L.O. original record, at the location of the found original stone in mound of stones, set 30 inch long 2 inch I.D. aluminum pipe 22 inches in ground to bedrock with 3 1/4 inch aluminum cap marked as shown:

Marked new bearing trees:

a 25" dbh Juniper bears South 67 1/2° West, 51.4 ft.
scribed 1/4S22BT;
a 12" dbh Juniper bears South 64 1/2° East, 58.5 ft.
scribed 1/4S23BT.

Nailed brass washer marked "LS 1026" in lower blaze.



Magnetic
Declination

20° EAST

Raised a mound of stones 2 1/2 foot base to top of cap and buried the original stone NORTH of cap.
Set steel post with sign 54-4 6 feet NORTH of and facing cap.
Painted 6 inch red band and faces red and nailed signs 54-3 and 54-4 on all bearing trees.

I hereby certify the above corner monument was re-established as herein described on JULY 13, 1982.

Office of Surveyor County of Grant
State of Oregon I hereby certify that the within instrument was filed in this office
for record on the 3 day of Sept, 1982
Robert L. DeGott by David B. Armstrong
(COUNTY OFFICIAL) (DEPUTY)

