

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. A-23

History of original corner establishment:

NONE. This corner has been amended to the senior line. See Index No. A-23 AM for the full history.

DIAGRAM
T13S R27E

1/4 S1
T14S R27E
1993
PLS 2405

Description of Corner Evidence Found:

NONE. This is the amended position to the senior line. See Index No. A-23 AM for evidence found.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the point of intersection on the Senior Line I set a 2-1/2"x30" aluminum pipe with 3-1/4" aluminum cap, stamped as shown in the DIAGRAM, 26" in the ground.

From Which:

White Fir, 14" dia., bears S39°30'W, 17.1 ft., scribed: 1/4 S1 BT
White Fir, 10" dia., bears S03°15'W, 12.2 ft., scribed: 1/4 S1 BT
White Fir, 24" dia., bears S41°15'E, 44.7 ft., scribed: 1/4 S1 BT
Ponderosa Pine, 12" dia., bears S69°15'E, 52.6 ft., scribed: 1/4 S1 BT

Measurements to BT's taken with a magnetic compass, declination 20° East, and a nylon clad steel tape. Set steel fence post with Land Survey Monument (54-9) and Property Boundary (54-2) signs 5' east and west of the monument. Nailed a brass washer stamped PLS 2405 on blaze above BT scribe as taken this survey. Nailed Bearing Tree (54-3) signs above blaze and Land Survey Monument (54-9) signs on back of each tree as required. Painted a 6" red band above Bearing Trees signs.

The original corner bears S00°20'19"W, 17.57 ft.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 26, 1989
SUSAN E. NEWSTETTER
2405

This work was performed by:
Susan E. Newstetter PLS 2405
Witnessed by: Rick Saul, Brad
Cates and D. Mitchell Ferguson
July 26, 1993
Refer to Grant Co. Survey No.: 1279

Renewal Date: 12/31/94

Office of Surveyor County of Grant
State of OR hereby certify that the within instrument was
filed in this office for record on the 21 day of Jan, 19 94
Robert D. Bayart by _____
(COUNTY OFFICIAL) (DEPUTY)