

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. C-19

History of original corner establishment:

None. Corner established this survey.

DIAGRAM
T14S R27E
C 1/4
•
S 2
1993
PLS 2405

Description of Corner Evidence Found:

None. Corner established this survey.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2-1/2"x30" aluminum pipe with 3-1/4" aluminum cap, stamped as shown in the DIAGRAM, 10" in the ground and raised a mound of stone around the monument.

From Which:

White Fir, 22" dia., bears N36°45'E, 5.8 ft., scribed: C1/4 S2 BT
White Fir, 20" dia., bears S60°15'E, 30.7 ft., scribed: C1/4 S2 BT
White Fir, 12" dia., bears S44°30'E, 29.4 ft., scribed: C1/4 S2 BT
Ponderosa Pine, 20" dia., bears S46°15'W, 1.7 ft., scribed: C1/4 S2 BT

Measurements to BT's taken with a magnetic compass, declination 20° East, and a nylon clad steel tape. Set steel fence post with Land Survey Monument (54-9) and Property Boundary (54-2) signs 5' north and east of the monument. Nailed a brass washer stamped PLS 2405 on blaze above BT scribe as taken this survey. Nailed Bearing Tree (54-3) signs above blaze and Land Survey Monument (54-9) signs on back of each tree as required. Painted a 6" red band above Bearing Trees signs.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 29, 1989
SUSAN E. NEWSTETTER
2405

This work was performed by:
Susan E. Newstetter PLS 2405
Witnessed by: Rick Saul, Brad
Cates and D. Mitchell Ferguson
August 9, 1993
Refer to Grant Co. Survey No.: 1279

Office of _____ County of _____
State of _____ I hereby certify that the within instrument was
filed in this office for record on the _____ day of _____, 19____
by _____
(COUNTY OFFICIAL) (DEPUTY)