

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. C-21.75 (line tree)

History of original corner establishment:

This line tree was originally established by William E. Campbell, in 1896, under GLO Contract No. 652, Surveyor General Field Notes state:

24.62 A tamarack 22 ins. diam, on line, I mark with 2 notches on N and S sides

DIAGRAM

W C

T14S R27E

Line Tree

S1 | S2

1993

PLS 2405

10.0'

Description of Corner Evidence Found:

Found a 36" western larch with healed hacks on north and south faces.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a witness corner southerly 10.0 ft., on line. Set a 2-1/2"x30" aluminum pipe with 3-1/4" aluminum cap, stamped as shown in the DIAGRAM, 26" in the ground.

From Which:

The following bearing trees are to the line tree itself:

White Fir, 12" dia., bears S81°15'E, 13.1 ft., scribed: LT S1 BT

White Fir, 14" dia., bears S33°45'W, 11.7 ft., scribed: LT S2 BT

Measurements to BT's taken with an Electronic Tacheometer with bearings based on the survey control network. Set steel fence post with Land Survey Monument (54-9) and Property Boundary (54-2) signs 5' south of the monument. Nailed a brass washer stamped PLS 2405 on blaze above BT scribe as taken this survey. Nailed Bearing Tree (54-3) signs above blaze and Land Survey Monument (54-9) signs on back of each tree as required. Painted a 6" red band above Bearing Trees signs.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 26, 1989
SUSAN E. NEWSTETTER
2405

This work was performed by:
Susan E. Newstetter PLS 2405
Witnessed by: Rick Saul, Brad
Cates and D. Mitchell Ferguson
August 6, 1993
Refer to Grant Co. Survey No.: 1279

Office of Surveyor County of Grant
State of OR hereby certify that the within instrument was
filed in this office for record on the 21 day of Jan, 1994
Robert D. Bowers by Robert D. Bowers
(COUNTY OFFICIAL) (DEPUTY)

C-21.75