

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

DEX No. E-22

History of original corner establishment:

None. Corner established this survey.

DIAGRAM
T14S R27E
S 1
W1/16—
S12
1993
PLS 2405

Description of Corner Evidence Found:

None. Corner established this survey.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2-1/2"x30" aluminum pipe with 3-1/4" aluminum cap, stamped as shown in the DIAGRAM, 26" in the ground.

From Which:

Lodgepole pine, 14" dia., bears N17°46'E, 51.2 ft., scribed: W1/16 S1 BT
White Fir, 28" dia., bears S18°48'E, 55.3 ft., scribed: W1/16 S12 BT

Measurements to BT's taken with an Electronic Tacheometer with bearings based on the survey control network. Set steel fence post with Land Survey Monument (54-9) and Property Boundary (54-2) signs 5' north and west of the monument. Nailed a brass washer stamped PLS 2405 on blaze above BT scribe as taken this survey. Nailed Bearing Tree (54-3) signs above blaze and Land Survey Monument (54-9) signs on back of each tree as required. Painted a 6" red band above Bearing Trees signs.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 28, 1989
SUSAN E. NEWSTETTER
2405

This work was performed by:
Susan E. Newstetter PLS 2405
Witnessed by: Rick Saul, Brad
Cates and D. Mitchell Ferguson
July 28, 1993
Refer to Grant Co. Survey No.: 1279

Renewal Date: 12/31/94

Office of Surveyor County of Grant
State of OR I hereby certify that the within instrument was
filed in this office for record on the 21 day of Jan, 1994.
Rick D. Saul by _____
(COUNTY OFFICIAL) (DEPUTY)