

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. J-9

History of original corner establishment:

This corner was originally established by Samual Lackland in 1881 under GLO Contract Number 415. Surveyor General Field Notes state:

Set basalt stone 18x12x7 ins. 12 ins. in ground for cor to Secs 8,9,16 & 17, marked with 4 notches on S and 4 notches on E edges from which

A Pine 20 in. diam. bears N2°E, 29 lks. dis. marked T14S R27E S9 BT

A Pine 30 in. diam. bears N25°W, 38 lks. dis. marked T14S R27E S8 BT

Raised mound of stone 2½ ft. high and 5 ft. base alongside.

In 1896, William E. Campbell, under GLO Contract Number 652, began his survey of the north line of Section 16 at this corner established by Samual Lackland. Campbell reports:

"..... determine a true meridian with the solar at the cor. of secs. 8,9,16 and 17, which is a basalt stone 12x7x6 ins. above the ground marked and witnessed by mound of stone so described by the surveyor general; but the bearing trees described in field notes of original survey are missing and no trees remain in reasonable limits for me to mark."

Description of Corner Evidence Found:

Found 18"x12"x10" stone with 4 notches on edge in a rock jack. Stone is not in it's original position, however fits well in terms of bearing and distance and I feel the rock jack was built over it's original position. I monumented the stone's position in the rock jack.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/4" aluminum cap, stamped as shown on the DIAGRAM, 12" in the ground and raised a mound of stone 3' dia x 1½' high around the monument. Place the original stone in mound along north side of the monument.

From Which:

Ponderosa Pine, 24" dia., bears N35°15'W, 72.6 ft., scribed: T14S R27E S8 BT
Mahogany, 6" dia., bears N47°30'E, 30.6 ft., scribed: T14S R27E S9 BT
Mahogany, 8" dia., bears S68°30'E, 7.8 ft., scribed: T14S R27E S16 BT
Ponderosa Pine, 16" dia., bears S55°45'W, 53.0 ft., scribed: T14S R27E S17 BT

Measurements to BT's taken with a magnetic compass, declination 20° East, and a nylon clad steel tape. Set steel fence post with Land Survey Monument (54-9) and Property Boundary (54-2) signs 5' east of the monument. Nailed a brass washer stamped PLS 2405 on blaze above BT scribe as taken this survey. Nailed Bearing Tree (54-3) signs above blaze and Land Survey Monument (54-9) signs on back of each tree as required. Painted a 6" red band above Bearing Trees signs and painted blaze red.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Susan E. Newstetter

OREGON
JULY 26, 1989
SUSAN E. NEWSTETTER
2405

This work was performed by:
Susan E. Newstetter PLS 2405
Witnessed by: D. Mitchell Ferguson
and Rick Saul
September 23, 1992
Refer to Grant Co. Survey No.: 1235

Exp: 12/31/94

Office of *Sumner* County of *Grant*
State of *OR* I hereby certify that the within instrument was
filed in this office for record on the *20* day of *Jan*, 19*93*

(COUNTY OFFICIAL)

(DEPUTY)

J-9

DIAGRAM

T14S R27E
S 8 | S 9
S17 | S16
1992
PLS 2405