


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

CORNER TO SECTIONS 27, 28, 33 & 34, T14S, R27E, W.M.

History of original corner establishment: SET BY J.W. LACKLAND

UNDER HIS CONTRACT DATED AUG. 19, 1881, CONTRACT NO. 415.

HIS NOTES STATE: SET BASALT STONE 14x7x6 INS. 9 INS IN GROUND FOR COR. TO SECS 27, 28, 33 & 34. MARKED WITH 1 NOTCH ON S. AND 3 ON E EDGES. RAISED MOUND OF STONE 2 1/2 FT. HIGH 5 FT. BASE ALONGSIDE.



Description of corner evidence found:

FOUND STONE 14"x7"x6", LEANING NLY., WITH 1 NOTCH ON S. AND 3 NOTCHES ON E. EDGES, ON S. SIDE OF STONE MOUND 4 FT. DIAM.

Description of monument and accessories I established to perpetuate the original location of this corner:

IN PLACE OF FOUND STONE MON. I SET A 3"x30" AL. PIPE WITH A 3 1/2" AL. CAP. STAMPED AS SHOWN ABOVE, BURIED STONE MON. ALONGSIDE, AND BUILT MOUND OF STONE AROUND IT. MY NEW ACCESSORIES ARE AS FOLLOWS:

- A 8" DBH JUNIPER, SCRIBED "T14S R27E S28 BT" BEARS N54 1/2° W, 118.8 FT.
- A 19" DBH. TRIPLE JUNIPER, SCRIBED "T14S, R27E S27 BT" BEARS N09° E, 207.8 FT.
- A 19" DBH. JUNIPER, SCRIBED "T14S R27E S33 BT" BEARS S18° W, 175.4 FT.
- A BASALT STONE IN PLACE, 19"x32"x8" HIGH ABOVE GROUND, CHISELED "+" BO" IN NW. FACE, BEARS S41 1/2° E, 62.3 FT.

DATE SET: 10-28-82

WITNESS: LUIS McLIND, DALE WRIGHT

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Victor M. McLind

OREGON
JULY 17, 1970
VICTOR M. McLIND
934

Office of.....Surveyor..... County of.....Grant.....
State of.....Oregon..... I hereby certify that the within instrument was filed in this office
for record on the.....16 day of.....Dec....., 19.....82
Robert D. Begett by.....
(COUNTY OFFICIAL) (DEPUTY)