

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

$\frac{1}{4}$ CORNER TO SECTIONS 25 AND 36, T14S, R27E W.M.

History of original corner establishment: SET BY J.W. LACKLAND

UNDER HIS CONTRACT NO. 415, DATED AUGUST 19, 1881

HIS NOTES STATE: SET BASALT STONE 18x12x8 INS 12 INS

IN GROUND FOR $\frac{1}{4}$ SEC. COR. MARKED $\frac{1}{4}$ ON N. FACE. RAISED

MOUND OF STONE 2 FT. HIGH 4 FT. BASE ALONGSIDE.

DIAGRAM

T14S R27E

$\frac{1}{4}$ $\frac{S 25}{S 36}$

1982

RLS 934

Description of corner evidence found:

NO EVIDENCE FOUND.

Description of monument and accessories I established to perpetuate the original location of this corner:

I SET THIS CORNER BY SINGLE PROPORTIONMENT.

AT CALCULATED LOCATION I SET A 3"x30" AL. PIPE WITH 3 $\frac{1}{2}$ " AL. CAP STAMPED AS SHOWN ABOVE, 18" IN GROUND, AND BUILT A MOUND OF STONE AROUND IT.

MY NEW BT'S ARE AS FOLLOWS:

A 14" D.B.H. JUNIPER, SCRIBED " $\frac{1}{4}$ S 36 BT" BEARS S 32° W, 135.8 FT.

A 19" D.B.H. JUNIPER, SCRIBED " $\frac{1}{4}$ S 25 BT" BEARS N 21 $\frac{1}{2}$ ° E, 173.1 FT.

DATE SET: 10-26-82

WITNESS: LUIS McLIND

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Victor M. McLind

OREGON
JULY 17, 1970
VICTOR M. McLIND
934

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 16 day of Dec, 1982
Robert D. Bagley by _____
(COUNTY OFFICIAL) (DEPUTY)