

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

CORNER TO SECS. 25 AND 36, T14S, R27E, AND SECS. 30 AND 31, T14S, R28E

History of original corner establishment: SET BY S.W. LACKLAND UNDER HIS CONTRACT NO. 415 DATED AUG. 19, 1881. HIS NOTES STATE: "SET BASALT STONE 20 X 12 X 10 INS 15 INS IN GROUND FOR COR. TO SECS 25, 30, 31 + 36 MARKED WITH 1 NOTCH ON S. AND 5 NOTCHES ON N. EDGES. FROM WHICH A PINE, 8 INS IN DIAM BEARS S 80° W 38 LKS DIS. MARKED T14S R27E BT RAISED MOUND OF STONE 2 1/2 FT. HIGH 4 1/2 FT BASE ALONGSIDE." RE-SET BY LEONARD CARTER UNDER SPECIAL INSTRUCTIONS DATED JAN. 24, 1938. HIS NOTES STATE: THE ORIG. COR. TO SECS. 25, 30, 31 AND 36, WHICH IS AN UNMARKED BASALT STONE 16 X 10 X 8 INS FIRMLY SET IN A RING OF STONE. AT POINT FOR CORNER, SET AN IRON POST 3 FT. LONG, 2 INS. DIAM. 28 INS IN THE GROUND, WITH THE ORIGINAL STONE DEPOSITED AT THE BASE, WITH BRASS CAP MARKED (AS SHOWN ABOVE) FROM WHICH: A YELLOW PINE, 15" DIAM BEARS S 53° W 39 LKS. DIST. BLAZE HEALED. I DO NOT OPEN. (OLD B.T.) A DOUGLAS FIR, 18" DIAM. BEARS N 28° E 93 LKS. DIST. MKD. T14S R 28 E S 30 BT (NEW B.T.) A WHITE FIR, 10" DIAM., BEARS S 36° E 40 LKS. DIST. MKD. T14S R 28 E S 31 BT (NEW B.T.) A YELLOW PINE, 12" DIAM., BEARS N 28° W 20 LKS. DIST. MKD. "T14S R 27 E S 25 BT (NEW B.T.) RAISE A MOUND OF STONE 3 FT. BASE 2 FT. HIGH W. OF COR.

DIAGRAM

T14S	
R27E	R28E
S25	S30
S36	S31
1939	

Description of corner evidence found:

FOUND 2" PIPE WITH BRASS CAP AS PER G.L.O. RECORD, LEANING S.E. 4°, LYING UNDER TWO 36" PINE WINDFALLS. FOUND B.T.'S AS FOLLOWS:

A 20" DBH P. PINE, GOOD SCAR, BEARS S 54 1/2° W 25.5 FT.

A 29" DBH. D. FIR, GOOD HEALED SCAR, BEARS N 28° E, 61.5 FT.

A 14" DBH W. FIR, GOOD HEALED SCAR, BEARS S 35° E, 26.3 FT.

A 15" DBH P. PINE WINDFALL, BADLY ROTTED, PARTLY HEALED FACE WITH SCRIBES VISIBLE, BEARS N 28° W 13.2 FT.

Description of monument and accessories I established to perpetuate the original location of this corner:

I STRAIGHTENED THE 2" PIPE TO ITS ORIGINAL LOCATION AND REBUILT THE STONE MOUND AROUND IT. I ALSO REMOVED WINDFALLS FROM OVER IT.

I BLAZED AND SCRIBED A NEW B.T. AS FOLLOWS:

A 21" D.B.H. D. FIR, SCRIBED "T14S R 27 E S 25 BT" BEARS N 75° W, 42.7 FT.

DATE: 8-23-82

WITNESS: DALE WRIGHT, LOUIS MCLIND

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Victor M. McLind

OREGON
JULY 17, 1970
VICTOR M. MCLIND
934

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 16 day of Dec, 1982
Robert D. Baggett by Victor M. McLind
(COUNTY OFFICIAL) (DEPUTY)