

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner established by: Bamford Robb, Deputy Surveyor, under Contract No. 357, dated July 2, 1880.

Surveyor General Record States: Set basalt stone 14x10x8 in mound of stone for 1/4 corner. From which:

A Mahogany 8" diam. bears S45°E, 39 lks dist.

T14S R33E

1/4

S8 | S9

2003

LS 2734

Description of corner evidence found:

Found a stone 15x10x8 inches, marked 1/4, broken in half, lying on its side in a ring of stones.

From which:

A 8" Mahogany bears S45°E, 26.1 ft., the lower blaze has been chopped out by an unknown person years ago. Where the upper portion of the blaze would be there are axe marks and a flat face about 12" high. The face has whetthered badly and no marks are visable.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
SEPTEMBER 19, 1995
JACK L. WATSON
2734

RENEWAL DATE: 6/30/2004

See Record Map of Survey No. 1672

Description of monument and accessories set at corner location:

I accept the marked corner stone position for this corner. I set a 2½"x30" aluminum pipe with attached 3½" aluminum cap and placed the original corner stone north and alongside the pipe. I built a mound of stone around pipe. The cap is stamped as shown in the diagram.

From which:

A 5" Juniper bears N65°E, 27.2 feet, marked X BT.

A 10" P.Pine bears S33°E, 17.3 feet, marked 1/4S9 BT.

A 6" Fir bears N10°W, 20.2 feet, marked 1/4S8 BT.

A 10" Mahogany bears N58°W, 4.7 feet, marked 1/4S8 BT.

I used a steel tape measuring to a 50d nail driven in the side center at the root crown of the BT's and magnetic compass, with 18° E. declination.

Date: August 4, 2003

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 8 day of Aug, 2003.
Bamford Robb by Jack L. Watson
(COUNTY OFFICIAL) (DEPUTY)