


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Set by B. Robb, contract 357, dated July 2, 1880.
North between sections 14 & 15, 80.0 chains set
basalt stone 10x8x6 in mound of stone for corner
to sections 10, 11, 14 & 15, from which:


- A fir 16in dia bears N 40° E 89 LKS dist
- A Mahogany 14 in dia S 80° W 49 LKS dist



Description of corner evidence found:

- A fir 40" dia scribed T14SR33ES11 BT N 40° E 58.7 ft
- A Juniper 40" dia scribed T14SR33ES15 BT S 80° W 32.3 ft

Description of monument and accessories established to perpetuate the original location of this corner:



At bearing and distance from original BT's I set a 3¼" aluminum cap on 2½" x 30" aluminum pipe 14" above ground in mound 4.0' x 1.0' marked

From which I mark new BT's:

- A Juniper 5" dia. bears N37°W, 21.2 ft. scribed T14SR33ES10 BT
 - A Juniper 8" dia. bears N23°E, 8.0 ft. scribed T14SR33ES11 BT
 - A Juniper 6" dia. bears S65°E, 29.9 ft. scribed T14SR33ES14 BT
 - A Juniper 5" dia. bears S70°W, 25.8 ft. scribed T14SR33ES15 BT
- Bearing and distances to center of tree with 20° variance.
Brass LS 1844 disc in lower blazes.

I hereby certify the above corner monument was re-established as herein described on November 12, 1981.



Office of... SURVEYOR County of... GRANT
State of... OREGON I hereby certify that the within instrument was filed in this office
for record on the 5 day of April , 1982
..... (COUNTY OFFICIAL) (DEPUTY)