

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

J-19

History of original corner establishment:

FIELD NOTES OF BAMFORD ROBB CONTRACT 357, DATED JULY 2, 1980
page 13

EAST on random line between secs 11 & 14
40.00 Set temporary $\frac{1}{4}$ sec cor
80.32 Intersected N&S line at the cor to secs 11-12-13-14
from which i run west on true line between secs 11&14
40.16 Set basalt stone 12X10X8 in mound of stone for $\frac{1}{4}$ sec cor

DIAGRAM

T 14 S R 33 E
 $\frac{1}{4}$ S 11
 S 14

Description of corner evidence found:

SEAR HED FOR FOUND NOTHING

FENCE ALONG LINE WITH MANY ROCK JACKS

Description of monument and accessories | established to perpetuate the original location of this corner:

At single proportionate distance along east-west line. Set a 3 inch aluminum cap on a $2\frac{1}{2}$ inch X 30 inch aluminum pipe 24 inches above ground in a mound of earth and stone 5 X 2 feet CAP MARKED

From cap marked new BTs

A 15 inch diam Pine bears N 52° E 37.3 feet dist marked ($\frac{1}{4}$ S11) (BT)
A 10 inch diam Pine bears S 53° W 94.0 feet dist marked ($\frac{1}{4}$ S14) (BT)

bearing and distances to center of tree, LS washer in lower blaze

I here-by certify the above corner monument was re-established as herin described on June 19, 1982

T14S R33E

$\frac{1}{4}$ S 11
 S 14
1982
RDS 1844

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

David E. Scott

OREGON
JULY 13, 1979
DAVID E. SCOTT
1844

See CS 726

Office of.....SURVEYOR.....County of.....GRANT.....
State of.....OREGON....., I hereby certify that the within instrument was filed in this office
for record on the.....*2*.....day of.....*Sept*....., 19*82*.....
Robert D. Sargent by.....
(COUNTY OFFICIAL) (DEPUTY)

J-19