

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Set by B. Robb, contract 357, dated July 2, 1880.
North between sections 13 & 14, 80 chains set stone
10x8x6 in a mound of stone for corner to sections
11, 12, 13, 14 from which:

- A pine 36in dia bears N40°E 37 LKS dist
- A pine 28in dia bears N35°W 56 LKS dist
- A pine 18in dia bears S60°W 32 LKS dist

DIAGRAM

T14S	R33E
11	12
14	13

Description of corner evidence found:

N35°W, 37.0 ft, 30" PP, D & D scribed T14SR33ES11 BT
N40°W, 24.4 ft, 30" PP stump, scribed BT
S65°W, 20.0 ft, 24" PP stump, scribed T14SR33ES14 BT
At location from BT's 2 rocks 8x8x4 and 8x4x4.


Description of monument and accessories I established to perpetuate the original location of this corner:

At distance and bearing from original BT's, I set a 3¼" aluminum cap on a 2½" x 30" aluminum pipe, 12" above ground in mound 4.0'x1.0' marked

From which I mark new BT's:

- A PP 6" dia bears N35°W, 37.0ft distance scribed T14SR33ES11 BT
 - A PP 8" dia bears N80°E, 18.5 ft distance scribed T14SR33ES12 BT
 - A PP 8" dia bears S46°E, 40.0 ft distance scribed T14SR33ES13 BT
 - A PP 5" dia bears S2½°W, 20.5 ft distance scribed T14SR33ES14 BT
- Bearings and distances to center tree with 20° variance.
Brass LS 1844 disc in lower blazes.

I hereby certify the above corner monument was re-established as herein described on November 13, 1981.



**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

David E. Scott

OREGON
JULY 13, 1979
DAVID E. SCOTT
1844

Office of SURVEYOR..... County of GRANT.....
State of OREGON..... I hereby certify that the within instrument was filed in this office
for record on the 5 day of April, 1982
Robert D. Leggett by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

GPO—798-276

SEE AMENDED RE-MON SHEET
FILED SEPT 2, 1982

J-21