

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Set by B. Robb, Contract 357, Dated July 2, 1880

North between sections 13 & 18

80.00 ch. Set stone 16x14 x10 for corn.to secs 7,18,12&13
from which

A pine 30 in dia bears N 40°E 52 links dist
A pine 36 in dia bears S 50°E 63 links dist
A pine 43 in dia bears S 60°W 70 links dist
A pine 30 in dia bears N 45°W 76 links dist

DIAGRAM

T 14 S
R 33 E R 34 E
12 7
13 18

Description of corner evidence found:

Stone 14 x 14 x 10 in mound of 6 rocks , no marks

40 inch pine stump N 66°W, 52.6 feet scribed (BT)

Description of monument and accessories | established to perpetuate the original location of this corner:

At location of stone set a 3 $\frac{1}{4}$ inch aluminum cap on a
2 $\frac{1}{2}$ inch by 30 inch aluminum pipe 12 inches above ground marked

Buried stone on north side of cap and marked new bearing trees

T 14 S
R33E R34E
12 7
13 18
1982
RLS 1844

6 inch P pine N 52°W, 22.8 feet scribed T14SR33ES12 BT
6 " " " N 62°W 11.9 " " T14SR33ES13 BT
6 " " " S75°E 7.3 " " T14SR34ES18 BT
6 " " " N 25°E 13.9 " " T14SR34ES7 BT

Bearings and distance to center of tree, brass ls 1844 washer in lower blaze

I here-by certify the above corner monument was
re-established as herein described on November 7, 1981

See CS 726



Office of.....SURVEYOR..... County of.....GRANT.....
State of.....OREGON....., I hereby certify that the within instrument was filed in this office
for record on the.....2..... day of.....Sept....., 1982.....
.....Robert D. Baggett..... by.....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

SuperSedes SHEET FILED APR 15, 1982

GPO-798-276

J-25