

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Set by B. Robb, Contract 357, dated July 2, 1880.

Set as end of true line from west across township

80.00 chains set Basalt stone 14x12x10 with mound of stone


for corner to sections 13 & 24 from which:

A Pine 7 ins dia bears N 5°E 50 LKS DIST

A Pine 12 ins dia bears N10°W 46 LKS DIST

A Pine 8 ins dia bears S30°E 36 LKS DIST

A Pine 24 ins dia bears S40°W 83 LKS DIST



Description of corner evidence found:

20" PINE S40°E 24.5 ft. distance Blaze Partially Open (14SR34)

Stone 17 x 12 x 6 in mound with 3 notches on east edges.

Description of monument and accessories I established to perpetuate the original location of this corner:

At location of stone I set a 3 1/4" aluminum cap on 2 1/2" x 30" aluminum pipe 16" above ground in mound 5.0' x 1.3' marked

From which I marked new BT's:

A 6" PP bears N50°W 86.6 ft. scribed T14SR33ES13 BT


A 8" PP bears N27°E 50.3 ft. scribed T14SR34ES18 BT

A 6" PP bears S63°W 57.2 ft. scribed T14SR33ES24BT

Orig. 20" PP bears S40°E 24.5 ft. scribed (14SR34)

All distances and bearings to center of tree with 20° variance.

Brass LS 1844 disc in lower blazes.



I hereby certify the above corner monument was re-established as herein described on November 7, 1981.

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

David E. Scott

OREGON
JULY 13, 1979
DAVID E. SCOTT
1844

Office of SURVEYOR County of GRANT
State of OREGON I hereby certify that the within instrument was filed in this office
for record on the 5 day of April, 1982
Mark D. Scott by _____
(COUNTY OFFICIAL) (DEPUTY)