

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Set by S. Lackland Contract #357, Dated July 2, 1880
East on True line between Secs 18 & 19
80.00 Set stone 14x10x4 in mound of stone for cor to
secs 17-18-19&20 from which

DIAGRAM

T14S R34E
S18 S17
S19

- A Pine 15" ins dia, bears S2°W, 12 LKS dist.
- A Pine 14" ins dia, bears S12°E, 23 LKS dist.
- A Pine 36" ins dia, bears N35°E, 110 LKS dist.
- A Pine 8" ins dia, bears N15°W, 74 LKS dist.

Retraced by H. Angell, dated September 27, 1900, Contract #726.


Description of corner evidence found:

- Found Pine Stump N35°E, 72.6 ft; No Scribing
- Found Fir Stump N15°W, 48.8 ft; No Scribing
- Found Pine Snag S12°E, 15.2 ft; Scribing Chopped Off
- Found Pine Dead and Down S2°W, 7.9 ft; Scribing Chopped Off
- Original stone not found.

Description of monument and accessories I established to perpetuate the original location of this corner:

At corner location from BT's I set a 3 $\frac{1}{4}$ " aluminum cap on 2 $\frac{1}{2}$ " x 30" aluminum pipe 18" above ground in mound 4' x 1.5' marked from which I scribed new BT's:

- A Fir 8" in dia. bears N74°W, 9.0 ft. marked T14SR34ES18 BT
- A Fir 6" in dia. bears N75°E, 25.8 ft. marked T14SR34ES17 BT
- Bear and distance to center of tree with variance of 20°
- Brass LS 1844 disc in lower blazes.



I hereby certify the above corner monument was re-established as herein described on November 2, 1981.

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

David E. Scott

**OREGON
JULY 13, 1979
DAVID E. SCOTT
1844**

Office of.....SURVEYOR..... County of.....GRANT.....
State of.....OREGON....., I hereby certify that the within instrument was filed in this office
for record on the.....5..... day of.....April....., 1982.....
Robert D. Segelt by.....
(COUNTY OFFICIAL) (DEPUTY)