

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Set by S. Lackland, Contract #357 dated July 2, 1880.
East on true line between sections 17 & 20.
40.00 chains set stone 16x12x12 in mound of stone for $\frac{1}{4}$ section corner from which:

a pine 8 ins dia. bears N76°W 50 LKS Dist.

a pine 8 ins. dia. bears S75°E 27 LKS Dist.

Retraced in 1901 by H. Angell Contract #726, dated Sept. 27, 1900.

DIAGRAM

T14S R34E

$\frac{1}{4}$ S17

Description of corner evidence found:

N 75°W, 33 ft., found 8" Pine Scribed $\frac{1}{4}$ S BT., Dead and Down
S 75°E, 17.8 ft., found 8" Pine Scribing chopped off, Dead and Down.
Original stone not found.

Description of monument and accessories I established to perpetuate the original location of this corner:

At location from original BT's I set a $3\frac{1}{4}$ " aluminum cap on a $2\frac{1}{2}$ "x30" aluminum pipe, 4" above ground marked

From which I scribed new NT's:

A Fir 6" diameter brs N4°E, 20.0 ft, marked $\frac{1}{4}$ S17 BT

A Fir 8" diameter brs N77°E, 18.6 ft., marked $\frac{1}{4}$ S17 BT

Bearing and distance to center of tree using 20° var.


Corner 6 feet south of East-West fence.

Brass LS 1844 disc in lower blazes.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

David E. Scott

OREGON
JULY 13, 1979
DAVID E. SCOTT
1844



I hereby certify the above corner monument was re-established as herein described on November 11, 1981.

Office of...SURVEYOR..... County of...GRANT.....
State of...OREGON....., I hereby certify that the within instrument was filed in this office
for record on the 5 day of April, 1982
Robert H. Sabers by
(COUNTY OFFICIAL) (DEPUTY)