

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

**History of original corner establishment:**

Corner was established by Homer D. Angell, US Deputy Surveyor, during the original survey Contract No. 726 dated September, 1900. Intersect old line 2 chs East of cor of secs. 13 & 14. I destroy all marks on old cor referring to secs. 23 and 24. Set basalt stone 14x12x8 ins. 10 ins. in the ground for C. cor of secs. 23 & 24 marked with C.C. on S face and 3 notches on the S faces and 1 notch on E edges; from which  
A fir 30 ins diam bears S65°E, (27.1') 41 lks dist. marked T14SR34E S24 BT  
A pine 8 ins diam bears S61°W, (29.7') 45 lks dist. marked T14SR34E S23 BT

DIAGRAM

T14S R34E

S13

S23 | S24

1991  
PLS 699

Corner was monumented at the original corner location by Duane Griffith, PLS 644, during a retracement survey dated September, 1981. A marked stone set firmly in the ground set a 1"x30" iron pipe, with brass cap

A PP 24" bears S70°E, 91.7 feet

A white fir 14" bears S30°W, 55.9 feet

**Description of corner evidence found:**

Found BGA monument set by PLS 644 on the original closing corner which is 0.81 feet N0°22'20"W of the standard section line. Stamped AM on this monument for Amended Monument.

30" Douglas-fir (40' Broken Stub)(Scribing Visible)(1900 BT) bears at record Did not make a new measurement to this deteriorating tree.

25" Ponderosa pine (Good Condition)(Scribing Visible)(1981 BT) bears S73°E, 90.9 feet. Distance and bearing is from the new monument

17" White fir (Good Condition)(Scribing Visible)(1981 BT) bears S30°W, 55.3 feet. Distance and bearing is from the new monument

8" pine (1900 BT) not found.

**Description of monument and accessories I established to perpetuate the original location of this corner:**

Set a 2"x30" aluminum pipe with a 2½' aluminum cap, marked as shown in the diagram, 24" in the ground rock, on the standard section line as determined by survey. Built a mound of rock to be 30" in diameter by 6" high around the monument, from which new Accessories are:

A Silver DEEP bears N30°W, 3.0 feet buried 8" in the ground

An Orange DEEP bears N73°E, 2.7 feet buried 6" in the ground

Attached BT and an Attention signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being a solar observation that was made on the adjacent McCoy Cadastral Survey contract in 1987, to stamped brass washers nailed on new BTs in the scribed red-painted blazes or to the red-painted blazes or scars on old BTs. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 3.6 feet S and 3.7 feet E of the corner on the National Forest boundary lines. Attached Forest Boundary signs to each post and an Attention sign to the S post.

I, Leland L. Myers, 587 E. Auburn St., P.O. Box 98, Sumpter, OR 97877, do hereby certify that on October 4, 1991, I monumented the corner as herein described.



FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 30 DAY OF NOV, 1992

*Robert D. Sayers*

Grant County Surveyor



MAP OF SURVEY No. 1197