

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by S.W. Lackland & Bamford Robb, US Deputy Surveyors, during the original survey Joint Contract No. 357 dated July, 1880.

Set stone 30x24x16 for 1/4 sec cor from which

A pine 12 ins diam bears S60°E, (8.6')131ks dist

A pine 6 ins diam bears N4°E, (26.4')401ks dist

DIAGRAM

T14S R34E

SC

1/4 S13

1

1991

PLS 699

Description of corner evidence found:

Found the large stone, but due to the flakey condition of the rock surface no markings could be found. The SW bearing tree, which had the scribing erased by Homer Angell's 1901 survey, was found.

28" Ponderosa pine (Good Condition)(Scribing was erased in 1901)(1880 BT) bears S64°W, 9.0 feet.

6" pine (1880 BT) not found.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 2½" aluminum cap, marked as shown in the diagram, 26" in the ground, replacing the rock which is turned upside down and buried on the north side of the monument. Built a mound of rock to be 36" in diameter by 4" high around the monument, from which new BTs and

Accessories are:

9" Ponderosa pine bears N7°15'W, 75.3 feet scribed 1/4 S13 BT

6" Lodgepole pine bears N42°30'E, 83.6 feet scribed 1/4 S13 BT

A Pink DEEP bears S7°15E, 2.8 feet buried 6" in the ground

A Blue DEEP bears S42°30'W, 2.9 feet buried 8" in the ground

Attached BT and an Attention signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being a solar observation that was made on the adjacent McCoy Cadastral Survey contract in 1987, to stamped brass washers nailed on new BTs in the scribed red-painted blazes or to the red-painted blazes or scars on old BTs. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set a steel fence post 4.2 feet W of the corner with an Attention sign attached. The monument is not a National Forest property corner.

I, Leland L. Myers, 587 E. Auburn St., P.O. Box 98, Sumpter, OR 97877, do hereby certify that on October 6, 1991, I monumented the corner as herein described.



FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 30 DAY OF Nov, 1992

Robert D. Bayart

Grant County Surveyor



MAP OF SURVEY No. 1197