


History of original corner establishment:

Survey of 1901 by Homer D. Angell.
Set a sand stone, 12 x 10 x 6 ins, 8 ins. in the ground for 1/4 sec. cor. marked 1/4 on N. face; from which
A pine, 14 ins. diam., bears S. 55°E., 8 lks. dist., marked 1/4 S. 35, B.T.
A pine, 12 ins. diam., bears N. 37° 1/2 E., 32 lks. dist., marked 1/4 S. 26 B.T.



Description of corner evidence found:

A stone 12" x 10" x 6" marked 1/4 on N. side, set firmly in the ground.
Stone protrudes 6" above ground.
A 10" diam. pine windfall bears S. 53°E., 9 lks, with face & scribing visible.
A pine rootwad & rotted remains bears N. 32°E., 33 lks. dist.

Description of monument and accessories | established to perpetuate the original location of this corner:

In place of the original stone monument I set a 2 1/2" x 32" alum. pipe, surmounted by a 2 1/2" alum. cap; 26" in ground surrounded by a mound of stone.
A steel fence post bears East, 3.0 ft.
A lodgepole pine, 5: dia. bears N. 56°W., 31.8 ft. marked 1/4 S 26 B.T.
A Douglas fir, 10" dia. bears S. 13°W., 35.3 ft., marked 1/4 S 35 B.T.
A White fir, 11 1/2" dia. bears S. 09°W., 35.9 ft. marked 1/4 S 35 B.T.
A White Fir, 7 1/2" dia. bears N. 40°1/2 W., 24.5 ft. marked 1/4 S 26 B.T.


USDA-FS
Aluminum
Cap Marked

T. 14 S. R. 34 E.

$\frac{1}{4}$	$\frac{S\ 26}{S\ 35}$
---------------	-----------------------

OLPS 1805
1990

Mag Dec. 20° E. 10/26/90



Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 11 day of Feb, 1991
Robert D. Begett by _____
(COUNTY OFFICIAL) (DEPUTY)