


History of original corner establishment:

Survey of 1901 by Homer D. Angell
Set a Lava Stone, 12 x 8 x 8 ins., 8 ins
in the ground for 1/4 sec. cor marked
with 1/4 on W. face; from which
A pine, 14 ins. diam., bears
S.52°W., 33 lks. dist, marked
1/4 S. 35, B.T.
A pine, 18 ins. diam, bears N.46°E.,
53 lks. dist., marked 1/4 S.36, B.T.



Description of corner evidence found:

Original Stone 15 x 8 x 6 ins., laying on the ground.
A White Pine, 22" dia., bears S.52°W., 33 lks.
with face & scribing visible.
A White pine, 24" dia., bears N.46°E., 53 lks
with face & scribing overgrown.

Description of monument and accessories | established to perpetuate the
original location of this corner:

In place of original stone monument I
Set a 2 1/2" x 32" galvanized steel pipe,
Surmounted by a 2 1/2" Brass cap; 26 ins. in
the ground, surrounded by a mound
of stone. Original stone buried alongside.
A steel fence post bears North 3.0 ft.
used original B.T.'s.
A White Pine, 22" dia. bears S.52°W.
21.8 ft. dist., didn't re-mark.
A White Pine, 24" dia bears N.46°E., 35.0 ft.
didn't re-mark.
New B.T's. A White Fir 8 1/2" dia. bears N.64°W.,
30.1 ft. Marked 1/4 S 35 B.T.
A Engleman Sprice 5" dia. bears S.23°1/2E. 16.8 ft.,
Marked X B.T.


USDA-FS
Brass
Cap Marked

T. 14 S. R. 34 E.
1/4

S35 | S36

OPLS 1805
1990

Mag Dec. 21° E 10/29/90



Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 11 day of Feb, 1991.
Robert D. Bazz by _____
(COUNTY OFFICIAL) (DEPUTY)