

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. J-9

History of original corner establishment:

Corner was originally established by
G.R. Campbell in July, 1901, under
General Land Office Contract No. 724.
U.S. Surveyor Generals Notes State:
Set basalt stone 18x12x8 ins. 12 ins. in the
ground for cor of secs 8,9,16 & 17, marked
with 4 notches on S and E edges.

from which

A white fir 12 ins diam. bears N40°30'E., 49 lks dist marked T14S R35E S9 BT
A tamarack 30 ins diam. bears S26°30'E., 93 lks dist marked T14S R35E S16 BT
A yellow pine 22 ins diam. bears S50°W., 20 lks dist marked T14S R35E S17 BT
A yellow pine 28 ins diam. bears N50°W., 12 lks dist marked T14S R35E S8 BT

Description of corner evidence found:

Found 17"x10"x7" stone set vertical in the ground
with 4 notches on the South & East faces.

Found the remains of the original bearing trees for
Sections 8 & 17 at record measure from the stone.
Accepted the above described stone as the Section Cor.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown
on the **DIAGRAM**, SET in the ground, with the original stone North
alongside the pipe.
From Which: (New Bearing Trees)
A Fir 14" dia., Bears N67°W., 11.3 ft., scribed: T14S R35E S8 BT
A Fir 14" dia., Bears N43°E., 30.5 ft., scribed: T14S R35E S9 BT
A Fir 10" dia., Bears S40°E., 21.5 ft., scribed: T14S R35E S16 BT
A Fir 6" dia., Bears S31°W., 9.9 ft., scribed: T14S R35E S17 BT
Measurements to trees taken with a metal tape and magnetic compass,
with Declination set off 20 deg. East.
Nailed a brass washer stamped RLS 848 on blaze above BT scribe, Bearing
Tree Sign above blaze, and warning sign on back of each tree. Painted
a 6" red band at breast ht. around each tree. Set steel fence posts with
warning & Boundary Signs, North 6 ft. and East 5 ft. from the corner.

DIAGRAM

T14S R35E
S8|S9
-.-
S17|S16
1987
RLS 848

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1989
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson RLS 848
Mt. Vernon Oregon.
On: June 29, 1987
Refer to Map of Survey No. 1009

Office of Sumner County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 6 day of June, 1987
Robert D. Bayle by _____
(COUNTY OFFICIAL) (DEPUTY)