

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. L-9

History of original corner establishment:

Corner was originally established by
G.R. Campbell in July, 1901, under
General Land Office Contract No. 724.
U.S. Surveyor Generals Notes State:
Set basalt stone 24x12x8 ins. 18 is. in
the ground. for 1/4 sec. cor. marked 1/4
on W face.

DIAGRAM

T14S R35E
1/4
S171S16
1987
RLS 848

From which:

A red fir 36 ins diam. bears N50°E., 12 lks dist. mkd. 1/4 S16 BT
A red fir 15 ins diam bears N85°W., 6 lks dist. mkd. 1/4 S17 BT

Description of corner evidence found:

Found 22"x14"x8 stone with "1/4" on the West face,
set vert, with the top just under the ground.

From which:

A 40" fir with the blaze healed over bears Record,
N50°E., 7.9 ft.
Accepted the above described stone as the 1/4 Sec. Cor.

**Description of monument and accessories I established to perpetuate the
original location of this corner:**

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown
on the **DIAGRAM**, SET 28" in the ground and set the original stone
alongside the pipe.

From Which: (New Bearing Trees)

A Fir 12" dia., Bears N77°E., 17.0 ft., scribed: 1/4 S16 BT

A Fir 15" dia., Bears S33°W., 53.3 ft., scribed: 1/4 S17 BT

Measurements to trees taken with a metal tape and magnetic compass,
with Declination set off 20 deg. East.

Nailed a brass washer stamped RLS 848 on blaze above BT scribe, Bearing
Tree Sign above blaze, and warning sign on back of each tree. Painted
a 6" red band at breast ht. around each tree. Set steel fence posts with
warning & Boundary Signs, North & South 5 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1969
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson RLS 848
Mt. Vernon Oregon.
On: July 26, 1987
Refer to Map of Survey No. 1009

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 6 day of Nov, 1987
Robert D. Beyer by _____
(COUNTY OFFICIAL) (DEPUTY)