

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. N-9

History of original corner establishment:

Corner was originally established by G.R. Campbell in July, 1901, under General Land Office Contract No. 724. U.S. Surveyor Generals Notes State: Set a basalt stone 15x10x10 ins., 10 ins. in the ground, for cor of secs 16, 17, 20 and 21, marked with 3 notches on S and 4 notches on E edges.

from which:

A yellow pine 22 ins diam bears N67°E., 33 lks dist mkd. T14S R35E S16 BT
A yellow pine 22 ins diam bears S73°E., 31 lks dist mkd. T14S R35E S21 BT
A yellow pine 26 ins diam bears S49°W., 17.5 lks dist mkd. T14S R35E S20 BT
A yellow pine 22 ins diam bears N77°W., 16 lks dist mkd. T14S R35E S17 BT

DIAGRAM

T14S R35E
S17|S16
-.-
S20|S21
1987
RLS 848

Description of corner evidence found:

Searched a 100 ft. radius around center of search area, no evidence is found. Corner falls on a steep slope and the stone has eroded out.

No trace of the original bearing trees is found, a fire has been through the area. Corner is determined to be lost to erosion and fire, reestablished corner position at proportionate measure between the 1/4 corners found 1/2 mi. North, South, East and West.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 27" in the ground.

From Which:

Set 5/8" iron pins with plastic caps stamped SURVEY MARKER PLS 848 and steel guard posts with Bearing Tree and Warning signs, as follows:
N45°W., 10.0 ft., N45°E., 10.0 ft., S45°E., 10.0 ft. and
S45°W 10.0 ft. from the corner.

Measurements to accessories taken with a metal tape and magnetic compass with Declination set off 20 deg. East.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1909
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson RLS 848
Mt. Vernon Oregon.
On: Aug. 11, 1987
Refer to Map of Survey No. 1009

Office of.....*Surveyor*..... County of.....*Grant*.....
State of.....*Ore gon*....., I hereby certify that the within instrument was filed in this office
for record on the.....*6*..... day of.....*Nov*....., 19.....*87*.....
.....*Ronald D. Buzott*..... by
(COUNTY OFFICIAL) (DEPUTY)