

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. P-13

History of original corner establishment:

Corner was originally established by
G.R. Campbell in July, 1901, under
General Land Office Contract No. 724.
U.S. Surveyor Generals Notes State:
Set basalt stone 18x10x10 ins., 12 ins.
in the ground, for 1/4 sec. cor., marked
1/4 on W face;

DIAGRAM

T14S R35E
1/4
S211S22
1987
RLS 848

from which

A black pine, 16 ins diam bears S31⁰E., 85 lks dist mkd 1/4 S22 BT
A black pine, 17 ins diam bears N35⁰E., 14 lks dist mkd 1/4 S21 bt

Description of corner evidence found:

Found 16"x10"x6" stone with "1/4" on West face, set
vertical and solid.

No trace of the original bearing trees is found,
there were black pine (lodge pole) and have
deteriorated.

Accepted the above described stone as the 1/4 cor.

**Description of monument and accessories | established to perpetuate the
original location of this corner:**

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown
on the **DIAGRAM**. SET 30" in the ground and set the original stone North
alongside the pipe.

From Which:

A Fir 16" dia., Bears S52⁰W., 3.7 ft., scribed: 1/4 S21 BT

A Fir 14" dia., Bears N74⁰E., 18.2 ft., scribed: 1/4 S22 BT

Measurements to trees taken with a metal tape and magnetic compass,
with Declination set off 20 deg. East.

Nailed a brass washer stamped RLS 848 on blaze above BT scribe, Bearing
Tree Sign above blaze, and warning sign on back of each tree. Painted
a 6" red band at breast ht. around each tree. Set steel fence posts with
warning & Boundary Signs, North & South 4 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1993
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson RLS 848
Mt. Vernon Oregon.
On: Aug. 10, 1987
Refer to Map of Survey No. 1009

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 6 day of Nov, 1987
Robert D. B. Jett by _____
(COUNTY OFFICIAL) (DEPUTY)