

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by Homer D. Angell, US Deputy Surveyor, during the original survey Contract No. 726 dated September, 1900.
Set a basalt stone 18x12x10 ins. 12 ins. in the ground for cor of secs. 19, 24, 25 & 30 marked with 4 notches on N and 2 notches on S faces, from which

A pine 20 ins. diam., bears S67°E, (115.5')175 lks. dist. scribed T14SR35E S30 BT
A pine 20 ins. diam., bears S72°W, (100.3')152 lks. dist. scribed T14SR34E S25 BT
A pine 20 ins. diam., bears N19°W, (64.7')98 lks. dist. scribed T14SR34E S24 BT
A pine 20 ins. diam., bears N40°E, (42.9')65 lks. dist. scribed T14SR35E S19 BT

DIAGRAM

T14S	
R34E	R35E
S24	S19
S25	S30

1990
PLS 699

Description of corner evidence found:

Found a basalt stone with the proper markings firmly set in the ground and surrounded by rocks.

33" Ponderosa pine (Dead)(Scribing Visible)(1900 BT) bears S72°30'E, 111.4 feet.
33" Ponderosa pine (Good Condition)(Scribing Visible)(1900 BT) bears N18°W, 65.5 feet.
42" Ponderosa pine (Good Condition)(Scribing Visible)(1900 BT) bears N39°15'E, 40.1 feet.
20" pine (1900 BT) not found.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 2½" aluminum cap, marked as shown in the diagram, 24" in the ground, replacing the rock which is turned upside down and buried on the north side of the monument. Improved the existing mound with rock to be 34" in diameter by 6" high around the monument, from which new BTs are:

15" Ponderosa pine bears S58°E, 11.9 feet scribed T14SR35E S30 BT
13" Ponderosa pine bears S36°30'W, 46.6 feet scribed T14SR34E S25 BT

Attached BT and Attention signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being a solar observation that was made on the adjacent McCoy Cadastral Survey contract in 1987, to stamped brass washers nailed on new BTs in the scribed red-painted blazes or to the red-painted blazes or scars on old BTs. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.
Set steel fence posts 4.0 feet W, 5.6 feet N, 4.9 feet E and 3.3 feet S of the corner on the National Forest boundary lines. Attached Forest Boundary signs to each post and an Attention sign to the W post.

I, Leland L. Myers, 587 E. Auburn St., P.O. Box 98, Sumpter, OR 97877, do hereby certify that on November 16, 1990, I monumented the corner as herein described.

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 30 DAY OF Nov, 1992

Robert D. Bayless
Grant County Surveyor

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 9, 1965
LELAND LEE MYERS
699

MAP OF SURVEY No. 1197