

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by Homer D. Angell, US
Deputy Surveyor, during the original survey
Contract No. 726 dated September, 1900.
Set basalt stone 15x8x6 ins. 10 ins. in ground for
1/4 sec. cor. marked 1/4 on W face from which
A pine, 24 ins diam bears S14½°E, (117.5') 178 lks dist. marked 1/4 S30 BT
A pine, 12 ins diam bears S57½°W, (52.1') 79 lks dist. marked 1/4 S25 BT

DIAGRAM

T14S
R34E R35E

1/4
S25 | S30

1990
PLS 699

Description of corner evidence found:

Found an unmarked rock of the proper dimensions and at the record distance
and bearing from the downed BT. The other BT location falls in an old
logging road.

36" Ponderosa pine (Dead & Down)(Scribing Visible)(1900 BT) bears at SE record
12" pine, (1900 BT) not found.

**Description of monument and accessories I established to perpetuate the
original location of this corner:**

Set a 2"x30" aluminum pipe with a 2½" aluminum cap, marked as shown in the
diagram, 22" in the ground solid rock, replacing the rock which is turned
upside down and buried on the north side of the monument. Built a mound
of rock to be 30" in diameter by 8" high around the monument, from which
new BTs and Accessories are:

12" Juniper bears N31°E, 28.5 feet scribed 1/4 S30 BT

17" Ponderosa pine bears N67°45'W, 16.4 feet scribed 1/4 S25 BT

A Blue DEEP bears S31°W, 2.2 feet 8" in the ground

A Pink DEEP bears S67°45'E, 2.0 feet buried 8" in the ground

Attached BT and Attention signs to and painted a red band around each BT.
Bearings were turned from the control traverse with a theodolite, basis of
bearing being a solar observation that was made on the adjacent McCoy
Cadastral Survey contract in 1987, to stamped brass washers nailed on new
BTs in the scribed red-painted blazes or to the red-painted blazes or
scars on old BTs. Distances were measured from a 60d spike, with an
aluminum washer stamped PLS 699, which was driven into the side of each BT
approximately one foot above the ground.

Set steel fence posts 4.9 feet S and 6.1 feet N of the corner on the
National Forest boundary lines. Attached Forest Boundary signs to each
post and an Attention sign to the S post.

I, Leland L. Myers, 587 E. Auburn St., P.O. Box 98,
Sumpter, OR 97877, do hereby certify that on
November 16, 1990, I monumented the corner as
herein described.

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 30 DAY OF Nov, 1992

Robert D. Baggett
Grant County Surveyor



MAP OF SURVEY No. 1197