

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by Homer D. Angell, US Deputy Surveyor, during the original survey Contract No. 726 dated September, 1900.
 Set a basalt stone 16x12x10 ins. 11 ins. in ground for the corner to secs. 25, 30, 31 & 36 marked with 5 notches on N and 1 notches on S edges from which
 A white fir, 18 ins diam bears S35°E, (14.5')22 lks dist. marked T14SR35E S31 BT
 A white fir, 14 ins diam bears S41°W, (13.9')21 lks dist. marked T14SR34E S36 BT
 A white fir 12 ins diam bears N30°W, (15.2')23 lks dist. marked T14SR34E S25 BT
 A white fir 15 ins diam bears N86°E, (25.1')38 lks dist. marked T14SR35E S30 BT

DIAGRAM

T14S	
R34E	R35E
S25	S30
S36	S31

1990
PLS 699

Description of corner evidence found:

Found the stone with the proper markings laying in an animal trail about 1 foot NE of the corner location based on the bearing trees.
 19" White fir (20' Broken Stub)(Scribing Visible)(1900 BT) bears S42°45'W, 13.3 feet.
 15" White fir (Poor Condition)(Scribing Visible)(1900 BT) bears N33°45'W, 15.7 feet.
 16" White pine (Poor Condition)(Blaze Healed Over)(1900 BT) bears N86°E, 23.9 feet.
 18" white fir, (1900 BT) not found.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 2½" aluminum cap, marked as shown in the diagram, 28" in the ground, at a point of best fit from the BTs. The rock is turned upside down and buried on the north side of the monument. Built a mound of rock to be 18" in diameter by 2" high around the monument, from which new BTs are:

- 13" Douglas-fir bears N86°E, 14.7 feet scribed T14SR35E S30 BT
- 8" White fir bears S71°E, 19.8 feet scribed T14SR35E S31 BT
- 9" White fir bears S82°45'W, 30.6 feet scribed T14SR34E S36 BT

Attached BT and Attention signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being a solar observation that was made on the adjacent McCoy Cadastral Survey contract in 1987, to stamped aluminum washers nailed on new BTs in the scribed red-painted blazes or to the red-painted blazes or scars on old BTs. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.
 Set steel fence posts 4.8 feet E, 5.3 feet S, 4.5 feet W and 3.5 feet N of the corner on the National Forest boundary lines. Attached Forest Boundary signs to each post and an Attention sign to the E post.

I, Leland L. Myers, 587 E. Auburn St., P.O. Box 98, Sumpter, OR 97877, do hereby certify that on November 9, 1990, I monumented the corner as herein described.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Leland L. Myers

OREGON
JULY 9, 1965
LELAND LEE MYERS
699

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 30 DAY OF NOV, 1992

Robert D. Bayne
 Grant County Surveyor

MAP OF SURVEY No. 1197