

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by George R. Campbell, US Deputy Surveyor, during the original survey Contract No. 724 dated September, 1900. Set a basalt stone 15x12x10 ins. 10 ins. in the ground for 1/4 sec. cor. marked with 1/4 on N face from which

- A black pine 10 ins diam bears N11°E, (35.0') 53 lks dist. marked 1/4 S30 BT
- A tamarack 30 ins diam bears S51°E, (40.9') 62 lks dist. marked 1/4 S31 BT

DIAGRAM

T14S R35E

**S30
1/4—
S31**

**1990
PLS 699**

Description of corner evidence found:

Found the stump of one bearing tree. The corner area is near Grant County Road No. 14 and logging activity has occurred. There was no indication of the original corner stone.

- 28" Western larch (30" Stump)(Scribing Visible)(1900 BT) bears S51°E,, 40.9 feet.
- 10" black pine (1900 BT) not found.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 2½" aluminum cap, marked as shown in the diagram, 26" in the ground, at the point determined by the bearing trees. Built a mound of rock to be 30" in diameter by 4" high around the monument, from which new BTs and Accessories are:

- 12" White fir bears N46°15'W, 27.3 feet scribed 1/4 S30 BT
- 9" White fir bears S8°30'E, 34.4 feet scribed 1/4 S31 BT
- An Orange DEEP bears N8°30'W, 1.7 feet buried 8" in the ground
- A Pink DEEP bears S46°15'E, 2.5 feet buried 6" in the ground

Attached BT and an Attention signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being a solar observation that was made on the adjacent McCoy Cadastral Survey contract in 1987, to stamped brass washers nailed on new BTs in the scribed red-painted blazes or to the red-painted blazes or scars on old BTs. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground. Set steel fence posts 4.4 feet W and 4.7 feet E of the corner on the National Forest boundary lines. Attached Forest Boundary signs to each post and an Attention sign to the W post.

I, Leland L. Myers, 587 E. Auburn St., P.O. Box 98, Sumpter, OR 97877, do hereby certify that on November 19, 1990, I monumented the corner as herein described.

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 30 DAY OF NOV, 1992

Robert D. Bayless
Grant County Surveyor



MAP OF SURVEY No. 1197