

History of original corner establishment:

Survey of 1901 by George R. Campbell
At a point 800 ft. below sec.
cor., I set a basalt stone, 15 x 10 x 10
ins., 10 ins. in the ground, for 1/4
sec. cor., marked 1/4 on N. face; from which
A Yellow Pine, 36 ins. diam., bears N.37° 30"W.,
105 lks. dist., marked 1/4 S.29, B.T.
No other tree within limits; and raise a mound
of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.
Pits impracticable.

DIAGRAM

T. 14 S. R. 35 E.

$\frac{1}{4}$ S29
S32

Description of corner evidence found:

Original stone, tipped over but still in place, 17 x 12 x 8 ins.
marked 1/4 on North face.
A Ponderosa pine, 36 ins. dia. bears N.40°W. 106 lks. dist.
to the face of tree with faint scribing exposed.
(110 lks to center of tree)
A mound of stone bears North, 1 foot.

Description of monument and accessories | established to perpetuate the
original location of this corner:

In place of original stone monument I
Set a 2 1/2" x 30" alum. pipe, surmounted by a 3" dia.
alum. cap; 26" in the ground, surrounded by a mound
of stone. Original stone buried alongside.
A 6 ft. steel fence post bears West, 3.0 ft.
New B.T.'s .
A Ponderosa Pine 16 ins. dia., bears S.80°E.,
158.3 ft., marked 1/4 S 32 B.T.
Used original B.T.
A Ponderosa Pine 36" dia., bears N.40°W., 72.6 ft/
Remarked 1/4 S 29 B.T.
A Ponderosa Pine 19" dia., bears N. 73°W., 26.2 ft.
marked 1/4 S 29 B.T.
A double MT. Mahogany 9" dia., bears N.80°E. 34.2 ft.
marked 1/4 S 29 B.T.


USDA-FS
Standard
Cap Marked

T. 14 S. R. 35 E.

$\frac{1}{4}$ S29
S32

OPLS 1805
1990

Mag Dec 20° East 10/30/90



Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 11 day of Feb, 1991.
Robert D. Began by _____
(COUNTY OFFICIAL) (DEPUTY)