

History of original corner establishment:

Survey of 1901 by George R. Campbell
Set a basalt stone, 28 x 20 x 10 ins.,
21 ins. in the ground, for 1/4 sec. cor.,
marked 1/4 on W. face; from which
A black pine, 14 ins. diam., bears S.60° W.,
30 lks. dist., marked 1/4 S. 33, B.T.
A tamarack, 10 ins. diam., bears S.60°W.,
30 lks. dist., marked 1/4 S. 32, B.T.

DIAGRAM

T. 14 S. R. 35 E.
1/4

S32 S33

Description of corner evidence found:

Original stone 28" x 20" x 10", set firmly in the ground
marked 1/4 on west face.
A Tamarack windfall, S.63°W., 29 lks. with face & faint
scribing visible.
A White fir windfall, N.24°E., 46 lks. with burnt face
& possible faint scribing visible.
A Spruce, 16" dia. bears S.31°E., 8.3 ft. with face
& scribing visible - marked by Bert Udell. 7/23/59.

Description of monument and accessories | established to perpetuate the
original location of this corner:

In place of original stone monument I set a
2 1/2" x 30" alum. pipe surmounted by a 2 1/2" dia. alum.
Cap; 26" in the ground. Original stone buried alongside.
A steel fence post bears N. 3.0 ft.
New B.T.'s.
A Ponderosa Pine 26" dia. bears N.17°E., 49.0 ft.
marked 1/4 S.33 B.T.
A Western Larch 12" dia. bears N.39°W. 44.6 ft.
marked 1/4 S 32 B.T.
A White Fir 7 1/2" dia. bears S. 10°1/2 E. 4.4 ft.
marked 1/4 S 33 B.T.
A White Fir 5" dia. bears S. 33°W. 5.5 ft.
marked 1/4 S 32 B.T.

USDA-FS
Standard
Cap Marked

T. 14 S. R. 35 E.

1/4

S32 | S33

Mag. Dec. 20°E. 10/31/90

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 13, 1979
F. E. CALKINS
1805

OPLS 1805
1990

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 11 day of Feb, 1991
Robert D. Beyer by _____
(COUNTY OFFICIAL) (DEPUTY)