CERTIFIED RECORD OF LAND CORNER MONUMENTATION
C1/4 corner of Section 28, T14S, R31E, W.M.

History of original corner establishment:
Corner not previously established

CORNERSTONE SURVEYING INC
T14S R31E
C1/4
S28
2007

Description of corner evidence found:
NONE

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
SEPT 19, 1995
JACK L. WATSON
2734

Renewal Date 6/30/2008

Description of monument and accessories set at corner location:
Set a 5/8"x30" iron pin with attached 2" aluminum cap, surrounded by a mound of stone. The cap is stamped as shown in the diagram.

From which:
A 12" P. Pine bears N10°E, 35.4 ft., marked C1/4S28BT.
A 6" Fir bears S58°E, 15.5 ft., marked C1/4S28BT.
A 9" P. Pine bears S61°W, 49.0 ft., marked C1/4S28BT.
A 16" P. Pine bears N73°W, 51.2 ft., marked C1/4S28BT.

I used a steel tape measuring to a 50d nail driven in the side center at the root crown of the BT's and magnetic compass, with 18° E. declination.

Date: August 10, 2007

Reference Grant County Survey Map No. 1817.

Office of SURVEYOR County of GRANT
State of OREGON, I hereby certify that the within instrument was filed in this office for record on the 13 day of AUG, 2007.
Robert W Sargent by .....
(COUNTY OFFICIAL) (DEPUTY)

T-11