CERTIFIED RECORD OF LAND CORNER MONUMENTATION
S1/16 Section 27, T14S, R31E, W.M.

History of original corner establishment:
NONE

CORNERSTONE SURVEYING INC
S1/16
S28 | S27
2002

Description of corner evidence found:
NONE

REGISTERED
PROFESSIONAL
LAND SURVEYOR
OREGON
SEPTEMBER 19, 1995
JACK L. WATSON
2734
RENEWAL DATE: 6/30/2004

See Record Map of Survey No. 1650

Description of monument and accessories set at corner location:
At the corner position determined by survey I set a 5/8" x 30" iron pin with attached 2" aluminum cap. The cap is stamped as shown in the diagram.

From which:
A 13" P. Pine bears S24°E, 7.9 feet, marked S1/16S27BT.
A 12" Fir bears S41°W, 35.1 feet, marked S1/16S28BT.

I used a steel tape measuring to a 50d nail driven in the side center at the root crown of the BT's and magnetic compass, with 18° E. declination.

Date: November 15, 2002

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 27 day of Nov., 2002.
Robert D Barker by .....
(COUNTY OFFICIAL) (DEPUTY)

U-13