


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Mark A. Fullerton under his General Land Office contract No. 395. Surveyor General's records state:

"Set basalt stone 15" x 10" x 8 " in stone mound for 1/4 Cor."




Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2 1/2" X 30" aluminum pipe with 3" aluminum cap marked as shown: Set by single proportionate measure. Built stone mound around monument and tagged new bearing trees with a brass washer marked " L. S. 981."



New Bearing trees are marked as follows:

A 14 " twin Juniper bears N76° 45'W, 95.29 ft. scribed "1/4 S16 BT".

A 10 " Juniper bears S79° 12'E, 182.9 ft. scribed "1/4 S15 BT."

Witness to corner: David B. Clawson

REGISTERED PROFESSIONAL LAND SURVEYOR

*H. Leon Kennedy*

OREGON  
JULY 16, 1872  
H. LEON KENNEDY  
881

I hereby certify the above corner monument was set as herein described.

Office of... *Surveyor* ... County of... *Grant* ...  
State of... *Oregon* ... I hereby certify that the within instrument was filed in this office for record on the *25* day of *Feb* ... 19*81* ...  
*Robert D. Begett* by ...  
(COUNTY OFFICIAL) (DEPUTY)