CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Mark A. Fullerton under his General Land Office Contract No. 395. Surveyor General's records state:
"Set basalt stone 18 x 15 x 10 in stone mound for ¼ Sec. Cor.

DIAGRAM

T15S R26E
¼
S21 . S22

Description of corner evidence found:

Found stone 18" x 15" x 9" sitting upright in ring of 5 stones. Corner lies 61 feet south of South Fork of Wind Creek which bears N70 E. at this point for approx. 75' in each direction. (Original call 66' & N70 E)

Description of monument and accessories I established to perpetuate the original location of this corner

Set 2½" x 30" alum pipe with 3" alum cap marked as shown: T15S R26E
Built stone mound around monument. ¼
A 12" Douglas Fir bears N41 30'W, 32.5' scribed "¼S21 BT" S21 . S22
A 10" Douglas Fir bears N77 48'E, 73.6' scribed "¼S22 BT"
RLS 981 1980

REGISTERED
PROFESSIONAL
LAND SURVEYOR
OREGON
JULY 14 1972
H. LEON KENNEDY
981

Witness to corner: David B. Clawson

I hereby certify the above corner monument was set as herein described.

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 25 day of Feb, 19 81, at 10 o'clock a m., (signed)
Robert D Baggett by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/66)