


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

None. Corner not previously established.



J-22

T.E.B.29Bgl12

Description of corner evidence found:

None. Corner not previously established.

Description of monument and accessories established to perpetuate the original location of this corner:

At position determined by survey, set 2-1/2 inch O.D. X 30 inches long aluminum pipe 22 inches in ground to bedrock with 3 inch aluminum cap marked as shown:

Marked bearing trees:


A 7" Juniper bears North 61-3/4° East, 91.9 ft., scribed-W1/16S12BT;

A 16" Juniper bears South 8-3/4° West, 136.0 ft., scribed-W1/16S13BT.

Raised stone mound 2-1/2 feet diam. to cap. Set steel post 4-1/2 feet East with sign 54-9 facing cap. Painted red band and faces red and nailed signs 54-3 and 54-9 to BT's. Nailed brass washer stamped "AS&E LS1026" to face of BT's.

I hereby certify that the above corner monument was established as herein described on May 20, 1987.

Witnesses: David B. Armstrong  
Shelby H. Griggs



REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*David B. Armstrong*

6/26/87 OREGON  
AUGUST 22, 1975  
DAVID B. ARMSTRONG  
1026

Office of Suwaya County of Grant  
State of Oregon, I hereby certify that the within instrument was filed in this office  
for record on the 6 day of Aug, 1987  
Robert D. Begett by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)