


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

None. Corner not previously established.



L-22
F.B.2 Pg.17

Description of corner evidence found:

None. Corner not previously established.

Description of monument and accessories I established to perpetuate the original location of this corner:

At position determined by survey, set 2-1/2 inch O.D. X 30 inches long aluminum pipe 18 inches in ground to bedrock with 3 inch aluminum cap marked as shown:

Marked bearing trees:


An 8" Ponderosa Pine bears South 46° West, 50.9 ft., scribed-CW1/16S13BT;

A 16" Ponderosa Pine bears South 46° East, 12.2 ft., scribed-CW1/16S13BT.

Raised stone mound 3-1/2 ft. diam. to cap. Set steel post 5 feet East with sign 54-9 facing cap. Painted red band and face red and nailed signs 54-3 and 54-9 to BT's. Nailed brass washer stamped "AS&E LS1026" to face of BT's.

I hereby certify that the above corner monument was established as herein described on May 22, 1987.

Witnesses: David B. Armstrong
Shelby H. Griggs



M.V.19-1/2°E.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

David B. Armstrong

6/26/87 OREGON
AUGUST 22, 1975
DAVID B ARMSTRONG
1026

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 6 day of Aug, 1987
Robert D. Boyett by _____
(COUNTY OFFICIAL) (DEPUTY)