


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

None. Corner not previously established.



L-23
F.B.2 Pg.18

Description of corner evidence found:

None. Corner not previously established.


Description of monument and accessories established to perpetuate the original location of this corner:

At position determined by survey, set 2-1/2 inch O.D. X 30 inches long aluminum pipe 18 inches in ground to bedrock with 3 inch aluminum cap marked as shown:

Marked bearing trees:

A 13" & 8" double Juniper bears South 83-1/2° East, 113.9 ft., scribed-C1/4S13BT;
An 18" Douglas Fir bears South 47° West, 100.6 ft., scribed-C1/4S13BT.

Raised stone mound 3 feet diam. to cap. Set steel post 5 feet North with sign 54-9 facing cap. Painted red band and face red and nailed signs 54-3 and 54-9 to BT's. Nailed brass washer stamped "AS&E LS1026" to face of BT's.



M.V.19-1/2°E.

I hereby certify that the above corner monument was established as herein described on May 22, 1987.

Witnesses: David B. Armstrong
Shelby H. Griggs

REGISTERED
PROFESSIONAL
LAND SURVEYOR

David B. Armstrong

6/26/87 OREGON
AUGUST 22, 1975
DAVID B. ARMSTRONG
1026

Office of Sumner County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 6 day of Aug, 1987
Robert O. Sargent by _____
(COUNTY OFFICIAL) (DEPUTY)