


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established by Samuel W. Lackland, Deputy Surveyor under G.L.O. Contract No. 384 dated March 29, 1881.

Surveyor General's records state:

S89°52'W on true line between Secs 13 & 24
39.92 Set basalt stone 18X7X6 in mound of stone for 1/4 Sec. Cor.



N-23
F.B.2 Pgs.21&22

Description of corner evidence found:


At assumed corner location found basalt stone 16"X8"X6" lying over on face, raised upright stone marked "1/4" on North face. Original stone in small mound consisting of 3 other stones.

Description of monument and accessories I established to perpetuate the original location of this corner:

At position of original stone, set 2-1/2 inch O.D. X 30 inches long aluminum pipe 15 inches in ground to bedrock with 3 inch aluminum cap marked as shown:

Marked bearing trees:

A 9" Ponderosa Pine bears South 27° East, 87.7 ft., scribed-1/4S24BT;
A 10" Juniper bears North 83° West, 19.5 ft., scribed-1/4S13BT.



M.V.19-1/2°E.

Deposited original stone North of cap and raised stone and earth mound 3 foot diam. to cap. Set steel post 3 feet West with sign 54-4 facing cap. Painted red band and faces red and nailed signs 54-3 and 54-4 to BT's. Nailed brass washer stamped "AS&E LS1026" to face of BT's.

I hereby certify that the above corner monument was re-established as herein described on May 19, 1987.

Witness: David B. Armstrong

REGISTERED
PROFESSIONAL
LAND SURVEYOR

David B. Armstrong

6/26/87 OREGON
AUGUST 22, 1975
DAVID B. ARMSTRONG
1026

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 6 day of Aug, 1987
Robert D. Baxst by _____
(COUNTY OFFICIAL) (DEPUTY)