

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

CORNER TO SECTIONS 3, 4, 9 & 10, T15S, R29E, W.M.

History of original corner establishment: SET BY S.W. LACKLAND

UNDER HIS CONTRACT NO. 384 DATED MARCH 29, 1881.

HIS NOTES STATE: SET STONE 24x16x12 IN MOUND OF STONE

FOR CORNER TO SECS. 3, 4, 9 & 10 FROM WHICH:

A FIR 26 IN DIA BEARS N89°W 7 LKS. DIST.

A FIR 10 IN DIA BEARS S81°E 9 LKS DIST.

DIAGRAM

T15S R29E	
S4	S3
S9	S10
1982	
RLS 934	

Description of corner evidence found:

FOUND STONE 21x14x13, STANDING CARDINAL WITH 3 NOTCHES ON W. EDGE AND A FAINT "+" ON TOP, FROM WHICH:

OBT, 30" DBH FIR, FACE PARTLY OPENED, SCRIBES "S4 T) R2" VISIBLE, BEARS N89°W, 4.8 FT.

OBT, 19" DBH FIR, NKE SEAR HAS BEEN PARTLY OPENED BUT NO SCRIBES VISIBLE, BEARS S45°E, 6.2 FT.

Description of monument and accessories I established to perpetuate the

original location of this corner: IN PLACE OF FOUND STONE MON. I SET A 3"x30" AL. PIPE

WITH A 3 1/2" AL. CAP STAMPED AS SHOWN ABOVE, 5" ABOVE GROUND, BURIED ORIG.

STONE ALONGSIDE, AND SET STONES AROUND CORNER. MY NEW BT'S ARE AS FOLLOWS:

A 13 1/2" DBH D. FIR SERIATED "T15S R29E S3 BT" BEARS N29°E, 40.3 FT.

A 13 1/2" D.B.H. D. FIR, SCRIBED "T15S R29E S10 BT" BEARS S37 1/2°E, 60.8 FT.

A 3 1/2" D.B.H. P. PINE, SCRIBED "T15S R29E S9 BT" BEARS S39°W, 60.7 FT.

DATE SET 110-7-82

WITNESS: DALE WRIGHT, LUIS McLIND

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Victor M. McLind

OREGON
JULY 17, 1970
VICTOR M. McLIND
934

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 16 day of Dec, 1982
Robert A. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)