

RECORD OF LAND CORNER MONUMENTATION

SE CORNER SECTION 35, T. 15 S., R. 29 E., W.M.

ORIGINALLY ESTABLISHED BY: Albert O. Eckleson, U.S. Deputy Surveyor

CONTRACT NUMBER: 328

CONTRACT DATE: June 20, 1879

SUBSEQUENT SURVEYS:

Remonumented by Carl E. Sundet, PLS, as shown on Map of Survey No. 705 filed November 6, 1981 in the office of the Grant County Surveyor.

27	26			26	25
34	35			35	36
34	35			35	36

ORIGINAL DESCRIPTION: Set post for corner to Secs 35 & 36 from which A Pine 48 in diam bears N15°E 39 lks dist; A Pine 30 in diam bears N60°W 140 lks dist

SUNDET'S DESCRIPTION: Fd: Evidence of original post in ground.

Ref: 50" P.P.B.T. dead and down N.15°E 39 lks (N.15°E 39 lks) scribed "S 36 15 R 29 BT"

37" P.P.B.T. alive and open N71°W 140 lks (N60°W - 140 lks) scribed "S 35 T 15 R 29"

Set AP 26" in ground. Comp. decl. 18° East

Ref: 11" P.P.B.T. N.88½°W., 16.5 ft.

13" P.P.B.T. N.36½°E., 48.1 ft.

EVIDENCE FOUND: Found a 2½" aluminum pipe with a 3¼" aluminum cap (marked as shown below), projecting 2" above ground with no mound of stone. All bearing trees are dead and down.

DESCRIPTION OF MONUMENTS AND ACCESSORIES SET AND METHODS USED:

I accept the found aluminum monument for the true section corner position.


From which, I SCRIBE THE FOLLOWING NEW BEARING TREES:

- ▶ A 26" dbh Douglas-fir bears S.32°E., 30.06 ft. marked "T16SR29ES1" in upper blaze and "BT" in lower blaze
- ▶ A 13" dbh western larch bears S.24°W., 11.26 ft. marked "T16SR29ES1" in upper blaze and "BT" in lower blaze

I also SET THE FOLLOWING REFERENCE POINTS:

- ▶ A 5/8"x30" iron pin driven flush with the ground bears N.45°E., 15.08 ft., with attached 2½" aluminum cap marked "RP 1 2021 PLS 69454"
- ▶ A 5/8"x30" iron pin driven flush with the ground bears N.43°W., 15.33 ft., with attached 2½" aluminum cap marked "RP 2 2021 PLS 69454"

MONUMENT MARKED:



Painted a 6 inch red band around the bearing trees, and also painted the blazes red. Attached USFS signs 54-3 and 54-9 to the bearing trees.

Distances to accessories were measured with a steel tape. Distances to bearing trees were measured to a 60d nail driven in the side-center right at the root crown of each tree, with an attached 1½" brass washer stamped "PLS 69454". Bearings were measured with a magnetic compass with 14° East declination.

A steel T post with USFS sign 54-2 attached bears North, 3.5 feet from corner, and a steel T post with USFS signs 54-2 and 54-4 attached bears East, 4 feet from corner.

RESTORATION BY, STAMP AND DATE:

Work Performed May 6, 2021 by:

Jason L. Hatfield, PLS
Vincent Kelly, Survey Tech
Doug Crawford

USDA FOREST SERVICE
NORTHEAST OREGON LANDS ZONE
1550 Dewey Avenue, Suite A
Baker City, OR 97814
(541) 523-1337

RECEIVED AND FILED
GRANT COUNTY SURVEYOR

JUN 24 2021

BY:

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
NOVEMBER 30, 2007
JASON L. HATFIELD
#69454

EXPIRES: 6/30/2023