

History of original corner establishment:

Corner was established by Deputies Banford Robb and Samuel W. Lackland in 1880, contract #357. Set: Post Marked: 18" Pine S40W--47 lks.; 16" Pine N60W--60 lks.

Corner was monumented by the BLM in 1978 from original evidence. See record field notes.

DIAGRAM

T14S R31E

1/4 $\frac{S31}{S6}$

T15S

Description of corner evidence found:

BLM iron post with a 3" brass cap firmly set 12" above ground in a mound of stone. Stamped:

Orig. 18" now 26" Ponderosa Pine S59W--31.0' Scribing visible on open double blaze.

Orig. 16" now 24" Ponderosa Pine N22W--39.4' Scribing visible on open double blaze.

BLM 6" now sawed Pine stump N67E--5.2'(record 4.6') Scribing visible.

T14S R31E

1/4 $\frac{S31}{S6}$

T15S

1978

Description of monument and accessories | established to perpetuate the original location of this corner: Marked:


8" Pine N40 $\frac{1}{2}$ W--15.0' Scribed 1/4 S31 BT with a 1" brass disk stamped PLS 896 nailed flush between the B and the T.

7" D-Fir S44E--26.6' Scribed 1/4 S6 BT with a 1" brass disk stamped PLS 896 nailed flush between the B and the T.


Painted bands and blazes on all BT's red and nailed 54-9 and 54-3 signs to BT's as needed.

Set guard post West with 54-2 and 54-9 signs.

Declination 20.



Larry D. Bishop



EXPIRES 11-22-97

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 16 day of Aug, 1996
Robert D. Bayett by _____
(COUNTY OFFICIAL) (DEPUTY)

See Map 1422