

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

A-5

History of original corner establishment:

Corner was established by Deputies Banford Robb and Samuel W. Lackland in 1880, contract #357.
Set: Stone 10"x10"x5". Marked: 54" Pine S80E--13 lks.
30" Pine N48E--41 lks.; 36" Pine S60W--90 lks.; 24" Fir N54W--109 lks.

Corner was monumented by the BLM in 1978 from original evidence. See record field notes.

DIAGRAM

T14S	R31E
S31	S32
S6	S5
T15S	

Description of corner evidence found:

BLM iron post with a 3" brass cap firmly set 6" above ground in a mound of stone. Stamped:

T14S	R31E
S31	S32
S6	S5
T15S	
1978	

Orig. 54" now 45" Ponderosa Pine snag S80E--12.9' Scribing visible on double blaze.
Orig. 30" now 36" Ponderosa Pine snag N48E--29.0' Scribing visible.
Orig. 24" now 32" sawed D-Fir stump N54W--68.7'(record 109 lks.) Scribing visible.
BLM 9" now 9" Juniper S34E--11.9'(record 17½ lks.) Scribing visible.
BLM 13" now 14" Ponderosa Pine S60W--8.9' Healed blaze.
BLM 7" now 7" Ponderosa Pine N69W--12.2' Scribing visible.
Guard post West with 54-2 and 54-9 signs.

Description of monument and accessories I established to perpetuate the


original location of this corner:

Marked:


11" D-Fir N12E--17.7' Scribed T14S R31E S32 BT with a 1" brass disk stamped PLS 896 nailed flush between the B and the T.

Painted bands and blazes on all BT's red and nailed 54-9 and 54-3 signs to BT's as needed.

Declination 20.



Larry D. Bishop



EXPIRES 11-23-97

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 16 day of Aug, 1996
Ronald D. Bishop by _____
(COUNTY OFFICIAL) (DEPUTY)

See MOS 1422.