

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

A-11

History of original corner establishment:

Corner was established by Deputies Banford Robb and Samuel W. Lackland in 1880, contract #357.

Set: Stone 14"x8"x6". Marked: 30" Pine N30E--46 lks.; 24" Pine S48W--45 lks..

Corner was monumented by LS 1017 in 1979 from original evidence. See record, 11-23-79

DIAGRAM

T14S R31E

1/4 $\frac{S33}{S4}$

T15S R31E

Description of corner evidence found:

2½" alum. pipe with a 3" alum. cap firmly set 6" above ground. Mound of stone North. Stamped:

Orig. 30" now 18" sawed, rotted Pine stump N28E--37.7' (record N30E--46 lks.) with axe marks.

Orig. 24" now 30" Ponderosa Pine S40W--29.7' (record S48W)

Scribing visible on opened upper blaze.

1979 9½" now 14" D-Fir S6W--20.4' Scribing visible on nearly healed dbl. blaze.

1979 18" now 18" D-Fir N11E--40.9' Scribing visible on nearly healed double blaze.

Guard post East with 54-2 and 54-4 signs.

T14S R31E

1/4 $\frac{S33}{S4}$

T15S R31E

LS 1017

1979


Description of monument and accessories I established to perpetuate the original location of this corner:

Marked:


7" Ponderosa Pine N3½E--13.5' Scribed 1/4 S33 BT with a 1" brass disk stamped PLS 896 nailed flush between the B and the T.

Painted bands and blazes on all BT's red and nailed 54-9 and 54-3 signs to BT's as needed.

Declination 20.



Larry D. Bishop



EXPIRES 11-23-97

Office of Surveyor County of Grant
State of OREGON, I hereby certify that the within instrument was filed in this office
for record on the 16 day of Aug, 1996
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)

See Nos. 1422