

History of original corner establishment:

Corner was established by Deputies Banford Robb and Samuel W. Lackland in 1880, contract #357.  
Set: Stone 11"x10"x8". Marked: 24" Pine S65W--67 lks.; 36" Pine N63E--84 lks..

Corner was monumented by the BLM in 1978 from original evidence. See record field notes.

**DIAGRAM**

T14S R31E  
1/4  $\frac{S34}{S3}$   
T15S

Description of corner evidence found:

BLM iron post with a 3" brass cap firmly set 12" above ground in a mound of stone. Stamped:

T14S R31E  
1/4  $\frac{S34}{S3}$   
T15S  
1978

Orig. 36" now rotted 36" Ponderosa Pine stump N82E--29.0' Scribing visible on small slab at base.

Orig. 24" now 26" Ponderosa Pine S73W--38.9' (record S70W) Scribing visible on open burnt double blaze.

BLM 11" now 14" Ponderosa Pine N12E--22.4' (record 52 lks.) Healed blaze.

BLM 7" now 11" Ponderosa Pine S20E--34.3' Healed blaze.

Guard post West with 54-2 and 54-9 signs.


Description of monument and accessories | established to perpetuate the original location of this corner:

Marked:


13" Ponderosa Pine N42½E--69.4' Scribed 1/4 S34 BT with a 1" brass disk stamped PLS 896 nailed flush between the B and the T.

Painted bands and blazes on all BT's red and nailed 54-9 and 54-3 signs to BT's as needed.

Declination 20.



*Larry D. Bishop*



EXPIRES 11-23-97

Office of Surveyor County of Grant  
State of Oregon, I hereby certify that the within instrument was filed in this office  
for record on the 16 day of Aug, 1996  
Robert D. Hagido by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)