

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. B/C-22

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor.

DIAGRAM

T15S R31E
CS-NW
1/64
S 1
1988
RLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this Cor.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SEI 26" in the ground.

From Which:

A Fir 10" dia., Bears N13°W., 7.5 ft., scribed: CS-NW 1/64 S1 B1

A Fir 10" dia., Bears S70°E., 2.9 ft., scribed: CS-NW 1/64 S1 B1

Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.

Nailed a brass washer stamped RLS 848 on blaze above B1 scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, 3 ft. East and 4 ft. South from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1988
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson RLS 848
Mt. Vernon Oregon.
On: March 22, 1988
Refer to Map of Survey No. 1034

Office of..... *Sumner* County of..... *Grant*
State of..... *Oregon* I hereby certify that the within instrument was filed in this office
for record on the..... *28* day of..... *Mar* , 19..... *89*
..... *Robert D. Dagon* by
(COUNTY OFFICIAL) (DEPUTY)